





# **Lehigh White Masonry Cement**

## **LEHIGH WHITE MASONRY CEMENT**

- Type S
- Type N







#### PRODUCT INFORMATION

Lehigh White Masonry Cement is a blend of white portland cement and finely ground white limestone, combined with process additions that enhance water retention, workability, boardlife and durability. Our masonry cement is manufactured to exacting standards to meet the ASTM C91 specification for Masonry Cements.

Lehigh White Masonry Cement is brighter, better-looking and more consistent. Combining it with clean white sand produces bright white mortar. When combined with colored sand and or pigments, masons can produce a wide a range of color schemes. Lehigh White Masonry Cement delivers unsurpassed design flexibility.

#### USE

When combined with 2 <sup>1</sup>/<sub>4</sub> to 3 parts masonry sand per masonry mortar specification ASTM C270, Lehigh White Masonry Cement yields Type N or Type S mortars for masonry construction. Our cement is specifically formulated to produce white or colored mortars that are consistent and superior quality.

Mortar produced with masonry cement can be used in any application where masonry mortar is specified.

#### **GREEN BUILDING**

Concrete masonry is resilient to manmade and natural disasters protecting life and reducing the need to for new materials and rebuilding. It is durable, long lasting and requires little maintenance. Masonry materials can be recycled for other uses or be put to use in new masonry projects. Entire existing masonry buildings and structures can be reused for the ultimate in sustainable design.

### **AVAILABILITY**

Lehigh White Masonry Cement is packaged in Florida, Georgia, Texas and Pennsylvania. It is widely distributed east of the Rocky Mountains. For technical assistance or more info on Lehigh White Cement products, visit us online at www.lehighwhitecement.com.

For orders call the Southeast Sales Office at 866.305.2427 or e-mail us at infosoutheast@lehighwhitecement.com

Lehigh White Cement Company / 3920 Pendola Pt. / Tampa, FL 33619 Phone: 813.248.4000 / Fax: 813.248.4005 / E-mail: infosoutheast@lehighwhitecement.com / www.lehighwhitecement.com

CAUTION Masonry Cement when dry is non-hazardous. When in contact with moisture (such as in eyes or skin) or when mixed with water to make concrete, mortar or grout, it becomes highly caustic and will burn (as severely as third-degree) the eyes or skin. Inhalation of dry Masonry Cement can irritate the upper respiratory system. For additional safety information, please see our Safety Data Sheets available online at www.lehighwhitecement.com or phone 610.366.4600.

WARRANTY The information and statements herein are believed to be reliable, but are not to be construed as a warranty or representation for which we assume legal responsibility. No other warranty, representation, or condition of any kind, expressed or implied (including NO WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), shall apply. Having no control over the use of cement, Lehigh White Cement will not guarantee finished work, nor shall they be liable for consequential damages.